


Reducción excéntrica

Reducción excéntrica
Reducción excéntrica



Referencia	Características	Unidades por caja	Medida	l1	hp (mm)	D1 D2	k1	k2	
K160504	-	1	50/40	35	37	50/40	20	20	
K160604	-	1	63/40	35	37	63/40	20	20	80
K160605	-	1	63/50	35	37	63/50	20	20	80
K160656	-	1	63/56	35	37	63/56	20	20	80
K160704	-	1	75/40	35	30	75/40	20	20	80
K160705	-	1	75/50	35	37	75/50	20	20	80
K160706	-	1	75/63	35	37	75/63	20	20	80
K160756	-	1	75/56	35	37	75/56	20	20	80
K160904	-	1	90/40	30	33	90/40	20	20	80
K160905	-	1	90/50	30	34	90/50	20	20	80
K160906	-	1	90/63	30	39	90/63	20	20	80
K160907	-	1	90/75	30	44	90/75	20	20	80
K160956	-	1	90/56	30	36	90/56	20	20	80
K161104	-	1	110/40	31	34	110/40	20	20	80
K161105	-	1	110/50	31	34	110/50	20	20	80
K161106	-	1	110/63	31	34	110/63	20	20	80
K161107	-	1	110/75	31	36	110/75	20	20	80
K161109	-	1	110/90	31	41	110/90	20	20	80
K161156	-	1	110/56	31	35	110/56	20	20	80

Reducción excéntrica

Referencia	Características	Unidades por caja	Medida	l1	hp (mm)	D1 D2	k1	k2	
K161206	-	1	125/63	35	37	125/63	20	20	80
K161207	-	1	125/75	35	30	125/75	20	20	80
K161209	-	1	125/90	35	32	125/90	20	20	80
K161211	-	1	125/110	36	36	125/110	20	20	80
K161256	-	1	125/56	35	37	125/56	20	20	80
K161611	-	1	160/110	28	36	160/110	20	20	80
K161612	-	1	160/125	32	36	160/125	20	20	80
K165604	-	1	56/40	35	37	56/40	20	20	80
K165605	-	1	56/50	35	37	56/50	20	20	80