

GSI-1

Separador de grasas

Separador de grasas



Referencia	Características	Unidades por caja	Medida
33100513	0,2 l/s – Ø ent. sal. 110	1	5 us. – vol. 100 l
33100514	0,4 l/s – Ø ent. sal. 110	1	10 us. – vol. 200 l
33100515	0,6 l/s – Ø ent. sal. 110	1	15 us. – vol. 300 l
33105111	1 l/s – Ø ent. sal. 110	1	20 us. – vol. 400 l
33105112	1 l/s – Ø ent. sal. 110	1	25 us. – vol. 600 l
33105113	3 l/s – Ø ent. sal. 110	1	35 us. – vol. 1200 l
ISO0416	10 l/s – Ø ent. sal. 200	1	200 us. – vol. 6096 l
ISO0417	12 l/s – Ø ent. sal. 200	1	250 us. – vol. 7693 l
ISO0418	14 l/s – Ø ent. sal. 200	1	300 us. – vol. 8350 l
ISO5114	4 l/s – Ø ent. sal. 125	1	50 us. – vol. 1549 l
ISO5115	5 l/s – Ø ent. sal. 140	1	80 us. – vol. 1884 l
ISO5116	6 l/s – Ø ent. sal. 140	1	100 us. – vol. 2560 l
ISO5117	7 l/s – Ø ent. sal. 160	1	150 us. – vol. 3273 l
ISO5118	8 l/s – Ø ent. sal. 160	1	180 us. – vol. 4035 l